

MASTER COPPO

Notified Body 0497
n°1525/07

General description: laminated coloured asphalt shingle

Descriere generala: sindrila bituminoasa laminata colorata

bituminous compound/compound bituminos	-		Blown bitumen	
length/lungime	EN 544	mm	1000	+/-3
width/latime	EN 544	mm	340	+/-3
thickness/grosime	-	mm	3,3/6,6	+/-10%
exposed area/suprafata expusa	-	mm	245	-

Physical-chemical properties/Proprietati fizico-chimice

weight/greutate	-	kg/m ²	13	+/-10%
mass of the fibreglass mat/masa fibra de sticla	-	g/m ²	125	+/-10%
bitumen /bitum	EN 544	g/m ²	>1300	-
granules single layer/granule per strat	EN 544	g/m ²	>1400	-
mechanical resistance/rezistenta mecanica MD/CMD	EN 544	N/ 5 cm	>800/>600	-
nail resistance/rezistenta la strapungere	EN 544	N	>150	-
granules adhesion/aderenta granulelor	EN 544	-g	<0,5	-

Fire behaviour/Comportamentul la foc

classification according/conform normei	EN 13501-5	B roof (t1)
classification according/conform normei	EN 13501-1	E

Wrapping/Ambalaj

type/tip	cartboard/carton
shingles for bundle/placi per pachet	9
m ² /bundle/mp per pachet	2
m ² /pallet/mp per palet	120

Pentru mai multe informatii accesati www.tegola.ro

Further info about company, product and roofing instruction on web site www.tegolacanadese.com

Tegola Romania SRL.
Sos.Pogonele, nr.18, Buzau, RO
Tel. +40 238 718181 - Fax +40 238 719191
e-mail: office@tegola.ro

TEGOLA 
innovation in building

Company certified according quality system ISO 9001 and environmental system ISO14001