

Prestige Compact Antique



Notified Body 0497
n°1765/07

General description: asphalt shingle with Prepatinated copper

Descriere generala: sindrila bituminoasa cu foita de cupru prepatinat



| | | | | |
|--|--------|----|----------------------|---------------|
| bituminous compound / compound bituminos | - | | Blown bitumen | |
| length / lungime | EN 544 | mm | 1000 | +/-3 |
| width / latime | EN 544 | mm | 340 | +/-3 |
| thickness / grosime | - | mm | 4,7 | +/-10% |
| exposed area / suprafata expusa | - | mm | 290 | - |
| copper thickness/ grosime foita de cupru | - | µm | 70 | +/-3 |

Physical-chemical properties / Proprietati fizico-chimice

| | | | | |
|---|--------|-------------------|------------------|---------------|
| weight / greutate | - | kg/m ² | 8,28 | +/-8% |
| mass of the fibreglass mat / masa fibra de sticla | - | g/m ² | 2*80 | +/-10% |
| bitumen single layer / bitum ner strat | EN 544 | g/m ² | >1700 | - |
| mechanical resistance MD/CMD /rezistenta mecanica | EN 544 | % | 1500/1500 | +/-15% |
| nail resistance / rezistenta la strapungere | EN 544 | N | >200 | - |
| peeling / exfoliere | EN 544 | N/cm | >5 | - |

Fire behaviour / Comportamentul la foc

| | | |
|---|------------|--------------------|
| classification according / conform normei | EN 13501-5 | B roof (t1) |
| classification according / conform normei | EN 13501-1 | C s2 d0 |

Wrapping / Ambalaj

| | |
|--|---------------------------|
| type / tip | cartboard / carton |
| shingles for bundle / placi per pachet | 14 |
| m ² /bundle / mp per pachet | 4,06 |
| m ² /pallet / mp per palet | 194,88 |

Further info about company, product and roofing instruction on web site www.tegolacandese.com
Pentru mai multe informatii despre companie, produse si informatii tehnice, accesati www.tegola.ro

Tegola Romania SRL.
Sos.Pogonele, nr.18, Buzau
Tel. +40 238 718181 - Fax +40 238719191
e-mail: office@tegola.ro



Company certified according quality system ISO 9001 and environmental system ISO14001