

Prestige ZT



Notified Body 0497
n°1766/07

General description: asphalt shingle with Zinc-Titanium
Gescriere generala: sindrila bituminoasa cu foita de Zinc-Titan



| | | | | |
|--|--------|----|----------------------|---------------|
| bituminous compound / compound bituminos | - | | Blown bitumen | |
| length / lungime | EN 544 | mm | 1000 | +/-3 |
| width / latime | EN 544 | mm | 340 | +/-3 |
| thickness / grosime | - | mm | 4,7 | +/-10% |
| exposed area / suprafata expusa | - | mm | 290 | - |
| Zinc-titanium thickness / grosime foita Zinc-Titan | - | µm | 100 | +/-10 |

Physical-chemical properties / Proprietati fizico-chimice

| | | | | |
|--|--------|-------------------|------------------|---------------|
| weight / greutate | - | kg/m ² | 8,28 | +/-8% |
| mass of the fibreglass mat / masa fibra de sticla | - | g/m ² | 2*80 | +/-10% |
| bitumen single layer / bitum ner strat | EN 544 | g/m ² | >1700 | - |
| mechanical resistance MD/CMD / rezistenta mecanica | EN 544 | % | 1500/1500 | +/-15% |
| nail resistance / rezistenta la strapungere | EN 544 | N | >200 | - |
| peeling / exfoliere | EN 544 | N/cm | >5 | - |

Fire behaviour / Comportamentul la foc

| | | |
|---|------------|--------------------|
| classification according / conform normei | EN 13501-5 | B roof (t1) |
| classification according / conform normei | EN 13501-1 | E |

Wrapping / Ambalaj

| | |
|--|---------------------------|
| type / tip | cartboard / carton |
| shingles for bundle / placi per pachet | 14 |
| m ² /bundle / mp per pachet | 4,06 |
| m ² /pallet / mp per palet | 194,88 |

Further info about company, product and roofing instruction on web site www.tegolacanadese.com
Pentru mai multe informatii despre companie, produse si informatii tehnice, accesati www.tegola.ro

Tegola Romania SRL.
Sos.Pogonele, nr.18, Buzau -
Tel. +40 238 718181 - Fax +40 238719191
e-mail: office@tegola.ro

TEGOLA[®]
CANADASE 

Company certified according quality system ISO 9001 and environmental system ISO14001